

RRC-SMB-CAR

Car Adapter DC/DC

P/N: 110041



Features:

- 90 Watt continuous output power (85W main-output + 5W USB-output)
- Ultra-compact and lightweight car adapter
- Wide input voltage range
- USB charging port
- Worldwide approvals
- High safety standards (e. g. protection against short circuit, over current, over voltage, over temperature)
- For use in cars and trucks
- To power RRC-SMB-UBC, RRC-SMB-MBC, RRC-SMB-FPC and RRC-SMB-DBC charger

Applications:

- Suitable for portable or mobile devices as well
- Simultaneous power for a battery charger and USB-compatible device

Characteristics

Input	
Voltage range	11.00 – 32.00VDC
Switch off voltage	10.00VDC
Stand-by current	Typically 40.00mA @ 11.00V input Typically 80.00mA @ 32.00V input
Input fuse	12.00A (in CLP)
Protection	Reverse polarity (input fuse in CLP), under voltage protection, over temperature protection (latch-off reset)

Output 1 (main)	
Voltage range	24.00VDC nominal
Power	85.00W max.
Initial set tolerance	±3% max.
Load regulation	-80.00mV max. / A
Line regulation	±1% max.
Ripple & noise	< 200.00V
Current limit	Constant current, 6.00A max.
Protection	Short circuit, over current protection (current limitation), over-voltage protection (latch-off reset), over temperature protection (latch-off reset)

Output 2 (USB)	
Voltage	5.00VDC nominal
Current / Power	1.00A max. / 5.00W max.
Total tolerance	±5% max.
Protection	Short circuit, over current protection

Environmental		
	Operation:	Storage:
Ambient Temperature	-20°C to 40°C	-40°C to 85°C
Pressure & Altitude	1200hPa to 795hPa max. 2000m above sea level	1200hPa to 115hPa max. 1500m above sea level
Humidity (non-condensing)	5% to 95% r.H.	5% to 95% r.H.

General	
Input connector	Cigarette lighter adapter (CLP)
Output connector (output 1)	DC-Plug OD 5.5mm ID 2.1mm
Output connector (output 2)	USB receptacle, Type A
Efficiency	Typical 96% at 100% load
MTBF	>20000hPa @ 25°C ambient temperature and G _B per MIL HDBK217F
Green procurement	RoHS 2011/65/EU + 2015/863/EU REACH 1907/2006 WEEE 2012/19/EU China RoHS SJ/T 11363-2006
Indicator green LED	On: power on Flashing: Failure Off: Power off
Ingress protection rating	IEC60529, IP40
Cooling	Convection cooled

Safety & EMC		
Regulatory approvals	Europe United Kingdom International USA & Canada Australia & New Zealand	CE UKCA CB Report IEC60950-1 cULus UL60950-1 RCM
Electromagnetic Emissions	Europe USA	EN55032 class B, EN55024 FCC15 class B
Electromagnetic Immunity	ESD immunity Electromagnetic field immunity EFT / Burst immunity test ISO-Impulses	IEC61000-4-2, 4kV contact / 8kV air IEC61000-4-3, 80-2700MHz, 3V/m, AM 80%/1kHz IEC61000-4-4, +/-1kV, 5/50ns ISO7637-2, pulses 1, 2a, 2b, 3a, 3b, 4

- other approvals on request

RRC-SMB-CAR

Mechanical Details	
Housing dimensions (LxWxH)	115 x 53.7 x 21.5mm, without cables and connectors
Input cable length	100cm ±5%
Output cable length	100cm ±5%
Weight	250g, with cables and connectors

Germany/Headquarters

RRC power solutions GmbH
Technologiepark 1
66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.com

USA

RRC power solutions Inc.
18340 Yorba Linda Blvd.,
107-437
Yorba Linda, CA 92886

Tel.: +1 714 777 3604
Fax: +1 714 777 3658
Email: usa@rrc-ps.com
Web: www.rrc-ps.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial
Centre 2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.cn

China

RRC power solutions Ltd.
Room 1306, C Building,
Tianan International building,
Renmin South Road, Luohu
District, Shenzhen 518021

Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.cn