

# RRC3570-4

Standard Battery Pack Li-Ion  
**25.48V / 16Ah / 408Wh**

Datasheet





### **Easy Swap**

Including pull-out handles to ensure effortless battery removal in two directions & easy handling.



### **Smart Status Check**

Integrated LED for State of Charge (SoC) and State of Health (SoH).



### **Fast Charging**

Certified for 1C charging – from 20% to 80% in just 35 minutes, twice as fast as the industry standard.



### **IP65 Protection**

Extra robust housing, protected against dust ingress and water jets from any directions.




### **SMBus & CANBus**

Flexibly choose the communication standard that best suits your application.

## **Characteristics & Benefits of the RRC3570-4 standard Li-Ion battery pack:**

- Worldwide approvals and certification of safety standards
- No development costs, fast time-to-market
- Easy to handle
- State-of-the-art lithium-ion cells
- High discharge performance
- JEITA charging profile optimization
- Numerous and redundant safety features
- 80% of initial capacity after 1.000 cycles

**Worldwide Approvals****No NRE****Fast Time-to-Market****Highest Safety****Highest Quality****Highest Performance****Worldwide Availability****No Obsolescence****Independent of Quantity****Extensive Accessories****Dual Sourcing Strategy****Design-In Support**

## Characteristics

General	
Delivery Status Battery Capacity	<30%
Compliance Information	IEC62133-2 / CE / UL2054 / CAN ICES-003(B) / NMB-003(B) / FCC / ICES / UKCA / PSE / KC / BSMI / GOST-R / CMIM / CCC / RCM / BIS UN 38.3 / RoHS / REACH <i>Pending: IEC62619/UL2271</i>
Operating Temperature	0°C to 45°C (charge) -20°C to 60°C (discharge)
Storage Temperature	-20°C to 60°C max. -20°C to 25°C recommended
Communication Interface	SMBus: SBS compliant Smart Battery Interface CANBus: CANopen implementation according CiA418
P/N	110338 Each battery has an individual serial number (S/N), which is located on the hardpack label for tracking & traceability.
Country of Origin	Vietnam




Electrical Parameters	
Nominal Voltage	25.48V
Nominal (Rated) Capacity	16Ah
Standard Charge Current	8.00A (0.5C)
Maximum Charge Current	16.00A (1.0C)
Discharge Current	30.00A
Peak Discharge Current	48.00A
Energy	408Wh
Inrush current*	max. 300A

Battery Dimensions	
Length	188.50mm ± 1.00mm
Width	85.00mm ± 0.50mm
Thickness	81.50mm ± 0.70mm
Weight	~ 2.08 kg
Contacts	+, - SMBus/CANBus Sys Detect
Ingress protection	IP65

Safety Features	
CUV (Cell Under Voltage)	Protection against deep discharge
COV (Cell Over Voltage)	Protection against overcharge
OTC (Over Temperature in Charge)	Protection against overheating while charging
OTD (Over Temperature in Discharge)	Protection against overheating during discharging
OCC (Over Current in Charge)	Protection against overcurrent while charging
OCD (Over Current in Discharge)	Protection against overcurrent during discharging
OL (Overload in Discharge)	Protection against overload during discharging
SCD (Short Circuit in Discharge)	Protection against short circuits during discharging

\* Capacitive loads may cause brief inrush current peaks during connection or start-up. Suitable inrush current limitation must be implemented in the application. For more information, please refer to [www.rrc-ps.com/faq](http://www.rrc-ps.com/faq)

**Recommended Accessories**

Type	Product	P/N	Application
Power Management Module 	RRC-PMM35	110297	Power management module for smart battery charging with automatic power source selection. Fits to the RRC35xx standard smart batteries.
Battery Mating Connector 	RRC-MC35-180-30 RRC-MC35-90-30	211947 212418	Mating connector for standard smart batteries from RRC. Suitable for RRC35xx batteries. Available for 90° or 180° PCB mounting.
Battery Charger 	RRC-SMB-PBC	110365	Desktop battery charger for RRC3570-4.



SETTING STANDARDS  
IN POWER SOLUTIONS

**Germany / HQ**

RRC power solutions  
GmbH

Technologiepark 1  
66424 Homburg / Saar

+49 6841 98090  
sales@rrc-ps.com

**USA**

RRC power solutions  
Inc.

18340 Yorba Linda  
Blvd.,  
Suite 107-437,  
Yorba Linda, CA 92886

+1 714 777 3604  
usa@rrc-ps.com

**Hong Kong**

RRC power solutions  
Ltd.

Flat F43, 7/F, Wah Lok  
Industrial Centre (Phase  
2), 31-35 Shan Mei  
Street, Fo Tan, N.T.

+852 2376 0106  
hkrrc@rrc-ps.cn

**China**

RRC power solutions  
Ltd.

Room 1306, C Building,  
Tianan International  
Building  
Renmin South Road  
Luohu District  
Shenzhen 518021

+86 755 8374 1908  
hkrrc@rrc-ps.cn

**Vietnam**

RRC POWER SOLUTIONS  
COMPANY LIMITED

Block C, Lot CN4  
Dinh Vu - Cat Hai Economic  
Zone, Dong Hai 2 Ward  
Hai An District, 180000  
Hai Phong City

vietnam@rrc-ps.com